

# STREET IMPROVEMENT PERMIT/ \$25.00

---

**NAME:** \_\_\_\_\_

**DATE:** \_\_\_\_\_

**ADDRESS:** \_\_\_\_\_

**RECEIPT:** \_\_\_\_\_

**PHONE:** \_\_\_\_\_

**GL Account No.** \_\_\_\_\_

## DESCRIPTION OF WORK TO BE DONE

	Measurement	Prop Owners Share Unit Price	Total
1. Sidewalk _____ Sidewalk Removal	_____	_____	\$ _____
2. Curb and Gutter _____ Curb and Gutter Removal	_____	_____	\$ _____
3. Driveway Approach _____	_____	_____	\$ _____
4. Other _____	_____	_____	\$ _____

### Special Conditions:

Contact the Murray City Street Superintendent for concrete removal, Russ Kakala # 801-270-2442.  
Contact the Engineering Department 24 hours prior to concrete placement, Brandon Richards # 801-270-2478  
For tree removal contact Murray City Power Department Operations Manager, Bruce Turner # 801-264-2716.  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_

Applicant agrees to meet all Murray City Public Works Road Cut Standards & Specification as published by Murray City Engineering Department.

**Property Owner Signature:** \_\_\_\_\_

**City Representative:** \_\_\_\_\_

# GENERAL REQUIREMENTS

---

Murray City will only remove sidewalk, curb and gutter or driveway approaches when the concrete is deteriorated or damaged and is creating a hazard.

After permit is submitted and fee is paid, the Engineering Department will contact and meet with the property owner on site to review damaged concrete to be removed, explain applicable specifications for placement and restoration. Resident is responsible to hire a licensed contractor for placement of new concrete at resident's expense. Resident is also responsible for landscape restoration.

- **Untreated Road Base.** Untreated road base must meet AASHTO M 145 classification A-1. Place material per (APWA Section 32 05 10). Road base shall be compacted to 95% of the modified proctor density as determined by ASTM 1557. **Do not use gravel as a substitute for untreated road base.** Compaction testing may be required and shall be conducted by a certified materials testing lab.
- **Sidewalk.** Residential sidewalk must have 4 inches of compacted road base. Concrete must be 5 inches thickness placed with 6 ½ Bag Class 4000 concrete, (APWA Section 03 30 04). Expansion must be placed every 50 feet.
- **Saw-cut Driveway Approach.** Saw-cut driveway approach must be done by a licensed concrete cutting company.
- **Residential Driveway Approach.** A residential driveway approach must have 6 inches of compacted road base. Concrete must be 6 inches thickness placed with 6 ½ Bag Class 4000 concrete, (APWA Section 03 30 04). **Minimum of (12') in width with a maximum of (30') in width.**
- **30" Curb and Gutter.** Curb and gutter must have 8 inches of compacted road base. Concrete must be placed APWA Plan No. 205 Type A curb and gutter. Concrete must be placed with 6 ½ Bag Class 4000 (APWA Section 03 30 04).
- **Concrete Placement.** Before any concrete is placed the resident or contractor must call for an inspection 24 hours prior to placement. It is the contractor's responsibility to adhere to Murray City Standards and Specifications regarding concrete placement. If Murray City Standards are not followed, the concrete done will be removed and replaced at the expense of the applicant.
- **Asphalt patchwork.** Asphalt patch work will be done by the Murray City Street Department or by an approved asphalt paving company.
- **Clean Up.** Upon completion of the excavation and patchwork the area shall be swept and returned to original condition.

For more information, contact the Engineering Department at (801) 270-2400.